



FP360 PUTTY CORD

FIRE RETARDANT PUTTY FOR DIFFICULT SERVICE PENETRATIONS

TECHNICAL SHEET 22/08/2025



KEY FEATURES

- CE-marked
- Fire classifications up to 120 minutes
- No emissions, environmental and user friendly
- Very easy to install
- Fire sealing around services with zero or minimal annular gaps (max. 10mm)

DESCRIPTION

Bostik FP360 Putty Cord is a silicon based fire rated putty, hand workable, re-usable and re-serviceable due to its non-setting properties. Bostik FP360 Putty Cord contains a low pressure intumescent for optimal fire protection.

APPLICATIONS

Bostik FP360 Putty Cord is designed to be easily fitted around service penetrations where the gap around the services is very small, or there is no gap at all so a conventional fire rated sealant is impossible or difficult to fit due to the required depth and backing material. The putty cords are fitted covering the gap around the services and does not need to fill the gap to the required dept. Bostik FP360 Putty Cord will reinstate the fire rating of the partition and prevent the passage of smoke and flames in a fire, whilst also limiting sound and air movement around the service.

FEATURES

- Certified to the latest European standards EN 1366-3
- CE marked to EAD 350454-00-1104
- Fire resistance up to 120 minutes for both integrity and insulation
- Fire sealing without any minimum annular width around services
- For cables, steel pipes, copper pipes and alupex pipes
- Gives service penetrations a high fire resistance in dry lining partitions and masonry or concrete walls and floors\
- Stops penetration of both cold and hot smoke
- Self-adhesive and very easy to apply without tools
- Unaffected by moisture: can be used in wet rooms
- Never hardens and ensures a tight fit
- Can be reshaped in other sizes if necessary
- Environment- and user friendly, contains no solvents or VOC's
- Very easy to install

METHOD OF USE

Before installing FP360 Putty cord ensure that the surfaces are clean, free from dirt, grease and other contaminants. To improve adhesion to porous substrates take a thumb size piece of Bostik FP360 Putty Cord and gently rub over the required installation mounting area (especially important in soffit applications). Place the Bostik FP360 Putty Cord around the services to seal the annular space as specified in the approvals or installation instructions. Press Bostik FP360 Putty Cord into the wall and services with your thumbs to form a fillet or V-shaped joint, ensuring good contact is made between the service penetration and the wall or floor. Before application consult the installation instructions and ETA to ensure to achieve the intended fire resistance.

LIMITATIONS

- Where Bostik FP360 Putty Cord is to be installed against surfaces that cannot tolerate direct contact; appropriate surface preparation should be made (contact Bostik for guidance in these cases).
- For paints sensitive to sealing compounds, priming with a PVA primer is recommended.
- As Bostik FP360 Putty Cord is silicon based, in cases where corrosion protection is a problem; some metals may require a barrier between the putty and the metal surface prior to this installation.

- Bostik FP360 Putty Cord is not paintable.

CERTIFICATION / TEST REPORTS

- ETA 21/0557
- UL-EU certificate
- Emicode EC1 Plus
- A+ French VOC regulation
- LEED certificate
- BREEAM certificate

STORAGE STABILITY

Shelf life is unlimited when stored in temperatures between +5 and + 30°C.

FURTHER INFORMATION AVAILABLE ON REQUEST

- Material safety data sheet
- Installation instructions FP360 Putty Cord

TECHNICAL DATA	
Base	Ready for use silicon based putty
Technical Approval	EAD 350454-00-1104
Fire rating	Up to 120 minutes depending on application
Density	1.55 g/ml
Colour	Red
Application temperature	+4°C to +40°C
Service temperature	-70°C to +120°C
Durability	Class Z2: intended use in internal conditions with humidity lower than 85% RH excluding temperatures below 0°C, without exposure to rain or UV
Working life	Under normal conditions 50 years
Form	Ø15 mm x 20 cm
Packed per	5 cords per carton, total length 1m
Article number	30615327

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Bostik Benelux BV
 Denariusstraat 11
 4903 RC Oosterhout
 T: +31 (0) 162 491000
www.bostik.com

BOSTIK HOTLINE

Smart help +31 (0) 162 491000



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.